



Data sheet

## MULTI CONSOLE IX43 R32



Compressor and fans DC Inverter

GOLDEN FIN Protection

4 Configurable air inlets and 2 outlet

Dehumidifier

Anti-cold function

Remote control

MODEL		GIA-MFI-12IX43R32		GIA-MFI-16IX43R32	
Power supply / Connection		V,R,HZ		220-240V (1 phase ~ 50Hz)	
<b>PERFORMANCE</b>					
Cooling capacity	Capacity	<b>kW</b>	3,52 (0,77 - 3,81)	4,80 (2,60~4,90)	
		<b>Btu/h</b>	12.000 (2.627~12.983)	16.500 (9.000~17.000)	
Heating capacity	Capacity	<b>kW</b>	3,81 (0,46~4,34)	4,90 (2,10~5,70)	
		<b>Btu/h</b>	13.000 (1.568~14.808)	17.000 (7.500~19.600)	
<b>FEATURES</b>					
Indoor unit	Sound power (H)	<b>dB(A)</b>	55	60	
	Sound pressure (H/M/L/SL)	<b>dB(A)</b>	43/41,5/35/25	42,5/39/35/25	
	Air flow	<b>m<sup>3</sup>/h</b>	512/480/370	560/480/400	
	Selectable temperature range	<b>°C</b>	17 - 30	17 - 30	
<b>DIMENSIONS AND WEIGHT</b>					
Indoor unit	Net dimensions (W×H×D)	<b>mm</b>	700×600×210	700×600×210	
	Gross dimensions (W×H×D)	<b>mm</b>	810×710×305	810×710×305	
	Net/gross weight	<b>Kg</b>	14,8 / 19	14,8 / 19	
<b>CONNECTIONS</b>					
Refrigeration pipe	Liquid - Gas	<b>Inch.</b>	1/4"-3/8"	1/4"-3/8"	
Electric connections	Electrical supply	<b>mm</b>	from the outdoor	from the outdoor	
	Interconnection	<b>mm</b>	5X1,5	5X1,5	
EAN CODE			8435483823587	8435483823594	

**Notes:**

Capacity data under standard conditions. Actual data will vary depending on where the equipment is installed and how it is used.

Sound pressure values are measured 1m away in a semi-anechoic chamber.

The dimensions of the electrical wiring are approximate, it should be calculated based on the conditions of the installation itself.