



MULTI DUCT IX43 R32



Golden Fin protection

DC Inverter compressor and fans

Reduced height

Timer

Condensate pump

Wired control

Easy to clean filter

Fresh air

MODELS			GIA-MDI-12IX43R32	GIA-MDI-18IX43R32
Power Supply	V,P,HZ		220-240V (1 Phase ~ 50Hz)	
PERFORMANCE				
Cooling	Capacity	kW	3,50 (1,48 - 4,40)	5,30 (2,40 - 6,00)
		Frig/h	3.010	4.560
		Btu/h	11.900	18.000
Heating	Capacity	kW	3,81 (0,85 - 4,65)	5,57 (2,20 - 6,50)
		Kcal/h	3.200	4.800
		Btu/h	13.000	19.000
CHARACTERISTICS				
Indoor unit	Sound power	dB(A)	59	60
	Sound pressure (H/M/L)	dB(A)	27,5/34,5/40	44/42/40
	Nominal static pressure (min - max)	Pa	0 - 60	0 - 100
	Air flow	m ³ /h	600/480/300	1.006/853/684
	Operating temperature	°C	17~30	17~30
Climatised perimeter (depending on room conditions)	m ²	25	40	
DIMENSIONS AND WEIGHT				
Indoor unit	Net dimensions (LxHxD)	mm	700x200x450	880x210x674
	Net weight	Kg	18	25,6
CONNECTIONS				
Refrigerant pipe	Liquid-Gas	inch	1/4" - 3/8"	1/4"-1/2"
Electrical connections	Supply	mm	from outdoor	from outdoor
	Connections	mm	5 x 1,5	5 x 1,5