



Technical data

CASSETTE IX43 R32

- On/Off contact and alarm



Golden fin protection



DC Inverter compressor and fan



Condensate pump



Remote control



Leak detector



Fresh air

MODEL

		GIA-MC6-12IX43R32		GIA-MC6-18IX43R32	
Power Supply	V,P,HZ	220-240V (1 Phase ~ 50Hz)			
PERFORMANCE					
Cooling	Capacity	kW	3,52	5,27	
		Btu/h	3.027	4.532	
Heating	Capacity	kW	4,10	5,56	
		Btu/h	13.000	19.000	
FEATURES					
Indoor unit	Sound power	dB(A)	51	56	
	Sound pressure	dB(A)	35/39/43	41/42/44	
	Air flow	m ³ /h	450/530/650	500/560/680	
	Operating temperature	°C	17~30	17~30	
DIMENSIONS AND WEIGHT					
Indoor unit	Net dimensions (WxHxD)	mm	570x260x570 647x50x647 (panel)	570x260x570 647x50x647 (panel)	
	Net weight cassette/panel	Kg	16,2 / 2,5	16,2 / 2,5	
CONNECTIONS					
Refrigeration piping	Liquid-Gas	inch	1/4" - 3/8"	1/4"-1/2"	
Electrical connections	Alimentation	mm	from outdoor	from outdoor	
	Interconnexion	mm	5 x 1,5	5 x 1,5	
EAN CODE			8435483814820	8435483814813	